

The X-1000+ is one of the most economical thermal transfer printers in its class. With a rugged all-metal construction and fast 4 inches per second printing speed, the X-1000+ provides efficiency and high reliability for medium-volume printing needs.

It has an 8-inches diameter label roll and 1182-foot length ribbon capacity for industrial standard throughput. The X-1000+ is supports all major barcode symbology including 2-D barcodes (PDF-417, Datamatrix and MaxiCode). Built-in 512K ROM and 512K RAM (upgradable to 1 MB) enable users to print long label formats (up to 45 inches).

The X-1000+ is supplied with free Windows software and Win95/98/2000/NT drivers for instant Plug and Play on delivery. It also supports popular programming languages for easy connectivity in different environments.

Optional accessories, including heavy duty cutters, peel-off kits, RAM and Flash memory cards, and stand-alone KDUs provide flexibility in the setup.



Specifications

Printing method	Direct thermal & Thermal transfer	
Printing resolution	203 dpi (8 dots/mm)	
Max printing speed	2~4 ips (51~104 mm/s)	
Max printing length	8" (203 mm)	
Max printing width	4.09" (104mm)	
Fonts	Int'l character sets standard from .049"~.23"H (1.25mm~6.0mm) 4 direction 0°~270° rotation	5 alpha-numeric fonts All fonts are expandable up to 24 x 24 Soft fonts are downloadable
Barcodes	Code 39, Extended Code 39 Code 128(Subset A,B,C) Codabar EAN-13, EAN-128, UPC, UPC-A, E 2&5 add on, POSTNET, German POST, Matrix 25	Code 93, Code 128 UCC Interleave 2 of 5, EAN-8 2&5 add on,
2D Barcodes	Maxicode, PDF-417	
Graphic	PCX bit map, GDI graphics	
Memory	512KB DRAM, 512KB Flash Memory	
Interfaces	RS-232 serial, Centronics parallel	
Media	Roll-feed, die-cut, continuous, fan-fold, tags, Ticket in plain paper or thermal paper Min width 1.0" (25 mm) Min length 0.4" (10 mm) Thickness .0025"~.01(.0635mm~.254mm) Max roll capacity 8" (203mm) OD	Max width 4.6" (117 mm) Max length 8" (203 mm) Core size 1.5"~3.0" (38mm~76mm) ID
Ribbon	Wax, Wax/Resin, Resin Ribbon roll-Max OD 3" (76mm) Ribbon width 1.3", 2.5", 3.3, 4.3" (33mm, 64mm, 84mm, 109mm)	Ribbon length- Max 1182" (360m) Code size- ID 1" core (25mm)
Compact size	W 9.8" x D 16.0" x H 10.2" (W 250x D 410 x H 260 mm)	
Weight	28.2 lbs (12.8 kgs)	
Power source	110/220 VAC ± 10%, 50/60 Hz	
Agency listing	CE, UL, CUL, FCC class A	
Operation environment	40°F ~ 100°F (4°C~38°C)	10~90% non condensing
Software	ARGOX PPLA & PPLB Language Label editing software – ArgoBar	Windows Driver (Win 31/95/98/NT) CODESOFT 4 XLT PLUS
Optional items	Cutter, Dispenser kit, Real time clock External 8"OD media stacker, ArgoNet print server	Extension SRAM memory, Extension flash memory, Standalone KDU - ArgoKee,